



Camshelving® Basics Series

Single Shelf Kits for Stationary Units

3 Shelf Depths

18" (460 mm), 21" (540 mm),
24" (610 mm)



6 Shelf Lengths

30" (760 mm), 36" (910 mm), 42" (1070 mm),
48" (1220 mm), 54" (1380 mm), 60" (1530 mm)

Shelf Kit includes:

Two Stationary Traverses, 8 Stationary Dovetails (4 ea. A & B),
Vented or Solid Shelf Plates to complete one shelf.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The light-weight, yet extremely durable composite material in Camshelving® Basics Series endures even the toughest environments and supports all food safety, HACCP and sanitation recommendations. Shelves up 48" (1220 mm) long hold up to 600 lbs. (272 kg) evenly distributed static weight. Shelves 54" – 60" (1380 mm – 1530 mm) long hold up to 500 lbs. (227 kg) each. Shelves connected by Corner Connectors hold up to 300 lbs. (136 kg) on a 30" (760 mm) to 48" (1220 mm) traverse.

Smart Design

Similar to other shelving products by Cambro, shelf plates can be easily removed, washed individually or in sections and placed in an open-end Camrack® (OETR314) and washed in a commercial dishwasher

Uncompromised Reliability

Resistant to scratching, peeling, warping and corrosion every component in Camshelving® Basics was rigorously tested for strength, reliability and performance. Functions in temperatures down to -36°F (-38°C) or warm environments up to 190°F (88°C).

Exceptional Value

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Camshelving® Basics features a lifetime warranty against rust and corrosion eliminating the need for unnecessary replacement costs.

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____



Four Shelf Unit with Vented Shelf Plates.



Vented Shelf Kit includes two Traverses and Vented Shelf Plates for one shelf.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

Optional Accessories

Includes Corner Connectors and Identification Tag. Both clip easily onto traverses.

Approvals



Does not include Wall Fastener, Seismic Foot, Corner Connector and ID Tag.

COMPONENT



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

2ACS

Camshelving® Basics Series

Single Shelf Kits for Stationary Units

3 Shelf Depths

18" (460 mm), 21" (540 mm),
24" (610 mm)



6 Shelf Lengths

30" (760 mm), 36" (910 mm), 42" (1070 mm),
48" (1220 mm), 54" (1380 mm), 60" (1530 mm)

Shelf Kit includes:

Two Stationary Traverses, 8 Stationary Dovetails (4 ea. A & B),
Vented or Solid Shelf Plates to complete one shelf.

Stationary – Shelf Kits with Vented Shelf Plates

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M)
30" (760 mm) Traverses				
CBSK1830V1	18" 460 mm	30" 760 mm	5.78 (0.96)	2,62 (0,03)
CBSK2130V1	21" 540 mm	30" 760 mm	6.24 (0.96)	2,83 (0,03)
CBSK2430V1	24" 610 mm	30" 760 mm	6.64 (0.96)	3,01 (0,03)
36" (910 mm) Traverses				
CBSK1836V1	18" 460 mm	36" 910 mm	7.15 (1.51)	3,24 (0,04)
CBSK2136V1	21" 540 mm	36" 910 mm	7.65 (1.51)	3,47 (0,04)
CBSK2436V1	24" 610 mm	36" 910 mm	8.20 (1.51)	3,72 (0,04)
42" (1070 mm) Traverses				
CBSK1842V1	18" 460 mm	42" 1070 mm	8.63 (2.03)	3,91 (0,06)
CBSK2142V1	21" 540 mm	42" 1070 mm	9.15 (2.03)	4,15 (0,06)
CBSK2442V1	24" 610 mm	42" 1070 mm	9.78 (2.03)	4,44 (0,06)
48" (1220 mm) Traverses				
CBSK1848V1	18" 460 mm	48" 1220 mm	9.02 (1.54)	4,09 (0,04)
CBSK2148V1	21" 540 mm	48" 1220 mm	9.67 (1.54)	4,39 (0,04)
CBSK2448V1	24" 610 mm	48" 1220 mm	10.45 (1.54)	4,74 (0,04)
54" (1380 mm) Traverses				
CBSK1854V1	18" 460 mm	54" 1380 mm	10.85 (2.57)	4,92 (0,07)
CBSK2154V1	21" 540 mm	54" 1380 mm	11.47 (2.57)	5,20 (0,07)
CBSK2454V1	24" 610 mm	54" 1380 mm	12.33 (2.57)	5,59 (0,07)
60" (1530 mm) Traverses				
CBSK1860V1	18" 460 mm	60" 1530 mm	12.00 (2.85)	5,44 (0,08)
CBSK2160V1	21" 540 mm	60" 1530 mm	12.90 (2.85)	5,85 (0,08)
CBSK2460V1	24" 610 mm	60" 1530 mm	13.91 (2.85)	6,31 (0,08)

Architect Specs

Posts:	Proprietary non-corrosive composite material.
Post Connectors:	Glass Filled Nylon.
Traverses:	Proprietary non-corrosive composite material.
Vented Shelf Plates:	Polypropylene.
Corner Connectors:	Glass Filled Nylon.
Adjustable Foot:	Glass Filled Nylon.
Seismic Foot:	Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided).
Wall Fastener:	Stainless Steel.
Dovetails:	Resin Nylon.
Wedges:	Resin Polypropylene.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

Stationary – Shelf Kits with Solid Shelf Plates

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M)
30" (760 mm) Traverses				
CBSK1830S1	18" 460 mm	30" 760 mm	6.55 (0.98)	2,97 (0,03)
CBSK2130S1	21" 540 mm	30" 760 mm	7.25 (0.98)	3,29 (0,03)
CBSK2430S1	24" 610 mm	30" 760 mm	7.80 (0.98)	3,54 (0,03)
36" (910 mm) Traverses				
CBSK1836S1	18" 460 mm	36" 910 mm	7.95 (1.42)	3,61 (0,04)
CBSK2136S1	21" 540 mm	36" 910 mm	8.75 (1.42)	3,97 (0,04)
CBSK2436S1	24" 610 mm	36" 910 mm	9.50 (1.42)	4,31 (0,04)
42" (1070 mm) Traverses				
CBSK1842S1	18" 460 mm	42" 1070 mm	9.60 (1.96)	4,35 (0,05)
CBSK2142S1	21" 540 mm	42" 1070 mm	10.60 (1.96)	4,81 (0,05)
CBSK2442S1	24" 610 mm	42" 1070 mm	11.40 (1.96)	5,17 (0,05)
48" (1220 mm) Traverses				
CBSK1848S1	18" 460 mm	48" 1220 mm	10.20 (1.51)	4,63 (0,04)
CBSK2148S1	21" 540 mm	48" 1220 mm	11.25 (1.51)	5,10 (0,04)
CBSK2448S1	24" 610 mm	48" 1220 mm	12.25 (1.51)	5,56 (0,04)
54" (1380 mm) Traverses				
CBSK1854S1	18" 460 mm	54" 1380 mm	12.15 (2.49)	5,51 (0,07)
CBSK2154S1	21" 540 mm	54" 1380 mm	13.45 (2.49)	6,10 (0,07)
CBSK2454S1	24" 610 mm	54" 1380 mm	14.50 (2.49)	6,58 (0,07)
60" (1530 mm) Traverses				
CBSK1860S1	18" 460 mm	60" 1530 mm	13.40 (2.76)	6,08 (0,08)
CBSK2160S1	21" 540 mm	60" 1530 mm	14.70 (2.76)	6,67 (0,08)
CBSK2460S1	24" 610 mm	60" 1530 mm	16.00 (2.76)	7,26 (0,08)

Corner Connector Set

CODE	DESCRIPTION	CASE LBS. (CUBE)	CASE KG. (CUBE M)
CBCC1	Right and Left	0.36 (0.05)	0,16 (0,00)

Case Pack: 1 set

Identification Tag

CODE	DESCRIPTION
CBID6	ID Tag 6" (15 cm)

Case Pack: 12 each

Standard Color

Brushed Graphite (580)

Approvals



Does not include Wall Fastener, Seismic Foot, Corner Connector and ID Tag.

COMPONENT



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003