# **CAMBRO**

### Camshelving® Elements Series

# Stationary Starter & Add-On Units 4 or 5 Vented and Solid Shelves

(3 Vented + 1 Solid or 4 Vented + 1 Solid)

HEIGHT	DEPTHS	LENGTHS
1	3	8
84"	18"	24" 48"
	21"	30" 54"
	24"	36" 60"
		42" 72"

#### • Starter Units include:

2 factory assembled post kits, 8 or 10 stationary shelf traverses, stationary traverse dovetails and shelf plates.

#### • Add-On Units include:

1 factory assembled post kit, 8 or 10 stationary shelf traverses, stationary traverse dovetails and shelf plates.

All units ship complete in 1 box.



#### Features & Benefits

- Designed to easily support the performance demands of a busy foodservice operation with medium to heavy storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Install solid shelf on bottom to prevent water/cleaning liquid from sloshing onto products. Install on top to protect product on lower shelves from cooler condensation.
- Posts and traverses are made of a revolutionary, extremely strong composite material. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Traverse dovetails attach easily to secure shelf traverses.
- Smooth polypropylene shelf plates contain Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation.
- Shelving Units interconnect in straight lines with shared posts.
  Uniquely engineered Post Connectors offer exceptional cross stabilization.
  No add-on clips or "S" hooks required.
- Use corner connectors to add shelves in corners or to install intermediate shelves between 2 starter units to maximize space.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.

Printed in USA. REV. 12/16

- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color Brushed Graphite (580).

Item No.	
Quantity	
ΔΙΔ File /	Sner No

Job




**Stationary Starter Unit** 

Stationary Add-On Unit

### 4 Shelf Unit Weight Bearing Chart

Single Unit Single Unit with Dunnage Stand Corner Unit with 2 Dunnage Stands



3200 lbs.

Maximum Unit Capacity 2800 lbs.

Maximum Unit Capacity 1800 lbs.

Unit Capacity capacity on bottom s

\* Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 54" and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

### **Approvals**



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Single Shelf Security Cage, Tray Slide Rack, and Shelf Divider Bars are not NSF listed.



### **Camshelving® Elements Series**

# Stationary Starter & Add-On Units 4 or 5 Vented and Solid Shelves

(3 Vented + 1 Solid or 4 Vented + 1 Solid)

## **VS4**

4-Shelf Units (3 Vented + 1 Solid)

**84**" HEIGHT





18"	
DEPTH	

LENGTH	CODE
24"	ESU182484VS4
30"	ESU183084VS4
36"	ESU183684VS4
42"	ESU184284VS4
48"	ESU184884VS4
54"	ESU185484VS4
60"	ESU186084VS4
72"	ESU187284VS4

22"	EA182484VS4
28"	EA183084VS4
34"	EA183684VS4
40"	EA184284VS4
46"	EA184884VS4
52"	EA185484VS4
58"	EA186084VS4
70"	EA187284VS4

21"

24"	ESU212484VS4
30"	ESU213084VS4
36"	ESU213684VS4
42"	ESU214284VS4
48"	ESU214884VS4
54"	ESU215484VS4
60"	ESU216084VS4
72"	ESU217284VS4

2"	EA212484VS4
28"	EA213084VS4
34"	EA213684VS4
10"	EA214284VS4
6"	EA214884VS4
52"	EA215484VS4
8"	EA216084VS4

EA217284VS4

24"

24"	ESU242484VS4
30"	ESU243084VS4
36"	ESU243684VS4
42"	ESU244284VS4
48"	ESU244884VS4
54"	ESU245484VS4
60"	ESU246084VS4
72"	ESU247284VS4

00"	
22"	EA242484VS4
28"	EA243084VS4
34"	EA243684VS4
40"	EA244284VS4
46"	EA244884VS4
52"	EA245484VS4
58"	EA246084VS4
70"	EA247284VS4

Color: Brushed Graphite (580).

Item No		
Quantity _		
AIA File / Sp	oec No	
Job		

## VS5

**5-Shelf Units** (4 Vented + 1 Solid)

LENGTH

22"

28"





CODE

EA182484VS5

EA183084VS5

EA183684VS5

LENGTH	CODE
24"	ESU182484VS5
30"	ESU183084VS5
36"	ESU183684VS5
42"	ESU184284VS5
48"	ESU184884VS5
54"	ESU185484VS5
60"	ESU186084VS5
72"	ESU187284VS5
24"	ESU212484VS5
30"	ESU213084VS5
36"	ESU213684VS5
42"	ESU214284VS5
48"	ESU214884VS5
54"	ESU215484VS5
60"	ESU216084VS5
72"	ESU217284VS5
24"	ESU242484VS5
30"	ESU243084VS5
36"	ESU243684VS5
42"	ESU244284VS5
48"	ESU244884VS5
54"	ESU245484VS5
60"	ESU246084VS5
72"	ESU247284VS5

<u> </u>	ENTOUGHTOO
40"	EA184284VS5
46"	EA184884VS5
52"	EA185484VS5
58"	EA186084VS5
70"	EA187284VS5
22"	EA212484VS5
28"	EA213084VS5
34"	EA213684VS5
40"	EA214284VS5
46"	EA214884VS5
52"	EA215484VS5
58"	EA216084VS5
70"	EA217284VS5
22"	EA242484VS5
28"	EA243084VS5
34"	EA243684VS5
40"	EA244284VS5
46"	EA244884VS5
52"	EA245484VS5
58"	EA246084VS5
70"	EA247284VS5

### **Optional Accessories**

- Corner Connector Sets
- ☐ Bottom Shelf Dunnage Stands (Low or Tall)
- ☐ Shelf Identification Tags
- Wall Fastener
- ☐ Seismic Foot
- ☐ Shelf Divider Panel
- ☐ Shelf Divider Bars (Straight or Angled)
- ☐ Tray Sliding Rack

Printed in USA. REV. 12/16

- ☐ Single Shelf Security Cage
- ☐ Shelf Traverses (Single or Double)
- ☐ Drying and Storage Cradles

### **Architect Specs**

Posts and Traverses: Proprietary non-corrosive composite material.

Post Connectors: Reinforced nylon.

Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.

Corner Connectors: Reinforced nylon. Adjustable Foot: Reinforced nylon. Traverse Dovetails: Reinforced nylon.

Post Connector Wedges: Reinforced polypropylene.

### **Approvals**



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Single Shelf Security Cage, Tray Slide Rack, and Shelf Divider Bars are not NSF listed.



D101609