CAMBRO

Camshelving® Premium Series

Full Wrap Security Cage Units 2 Vented Shelves

HEIGHTS 2	DEPTH 1	LENGTH 1
64 ¹ / ₂ " Stationary 67 ³ / ₄ " Mobile	26 ³ / ₄ "	501/4"

Note: Outside dimensions include cage.

Single Shelf Security Cage

18"	24"	42"
1	1	1
HEIGHT	DEPTH	LENGTH

• Full Wrap Stationary Security Cage Unit includes:

2 factory assembled stationary post kits, 4 shelf traverses, vented shelf plates and 1 each full wrap security cage. Ships in 2 boxes.

• Full Wrap Mobile Security Cage Unit includes:

2 factory assembled mobile post kits, 4 each premium swivel casters with total locking brake, 4 shelf traverses, vented shelf plates, and 1 each full wrap security cage. Ships in 2 boxes.

• Single Shelf Security Cage ships in 1 box.



Features & Benefits

- Security cages offer strong, secure storage for valuable products such as liquor, china, silverware or linens. Store perishable high value meat or fish products in cooler or freezer. Safely store flammable canned heat product used with chafing dishes and/or room service hot boxes.
- Full wrap security cage units, stationary or mobile, offer maximum storage with easy access to contents. Additional shelf kits may be ordered and added to unit at time of assembly. NOTE: Bottom shelf must be vented only.
- Single shelf security cage installs easily onto one shelf (vented shelf only) where needed. Fits perfectly on 24" x 48" shelf or longer. Requires 18" open space between shelves.
- Cages made of heavy duty, 304 stainless steel for use in any environment. Lock not included.
- Posts and traverses have a steel core and smooth polypropylene exterior for superior strength and durability. Traverse dovetails are molded into posts.
- Premium caster is made of highly durable, non-corrosive plastic with a 5" (12,7 cm) swivel, non-marking thermoplastic rubber wheel. Total locking brake locks both swivel motion and the wheel.
- Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised.
- Posts and traverses easily wipe clean. Traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color Speckled Gray (480).

Item No	
Quantity	
AIA File / Spec No.	
loh	



Stationary Full Wrap **Security Cage Unit**

Mobile Full Wrap **Security Cage Unit**




Single Shelf Security Cage

4 Shelf Unit

Weight Bearing Chart Single Unit **Mobile Unit**



3200 lbs. Maximum **Unit Capacity**



Maximum

Unit Capacity

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Tray Slide Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.



Camshelving® Premium Series

Full Wrap Security Cage Units 2 Vented Shelves **Single Shelf Security Cage**

HEIGHT

Full-Wrap Stationary Security Cage Unit

CODE		DIMENSIONS D x L x H
CPU244864SI	JPKG	26¾" x 50¼" x 64½"
Case Pack: 1	Color: Speckled	d Gray (480).

Full-Wrap Mobile Security Cage Unit

CODE	DIMENSIONS D x L x H
CPU244864SUPKG	26¾" x 50¼" x 67¾"

Case Pack: 1 Color: Speckled Gray (480).



AIA File / Spec No.

HEIGHT

Single Shelf Security Cage

CODE	DIMENSIONS D x L x H	
CSSC244818	25½" x 42½" x 18"	

Printed in USA. REV. 12/16

Case Pack: 1 Color: Silver (000).



Optional Accessories

Vented and Solid Single Shelf Kits

Architect Specs

Quantity

Posts and Traverses: Internal steel core, reinforced polypropylene exterior. Post Connectors: Reinforced polypropylene. Security Cage: Heavy duty, 304 stainless steel.

Shelf Plates: Reinforced polypropylene with Camguard™ antimicrobial.

Caster: Non-corrosive plastic body and brake with non-marking thermoplastic rubber wheel.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Tray Slide Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.



Information and specifications are subject to change without notice. Please confirm at time of order. © Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A. Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com