



Camshelving® Basics Plus Series

Stationary Starter & Add-On Units 4 Solid or 4 Vented and Solid Shelves

(3 vented + 1 solid)

HEIGHT	DEPTHS	LENGTHS
1	3	6
64"	18" 21" 24"	30" 48" 36" 54" 42" 60"

- **Starter Units include:**
2 factory assembled post kits, 8 stationary shelf traverses, stationary traverse dovetails and shelf plates.
- **Add-On Units include:**
1 factory assembled post kit, 8 stationary shelf traverses, stationary traverse dovetails and shelf plates.

All units ship complete in 1 box.

Features & Benefits



- Designed to easily support the performance demands of a busy foodservice operation with medium to heavy storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Install solid shelf on bottom to prevent water/cleaning liquid from sloshing onto products. Install on top to protect product on lower shelves from cooler condensation.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Breakaway left and right traverse dovetails snap apart and attach easily to secure shelf traverses to posts.
- Smooth polypropylene shelf plates contain Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation.
- Shelving Units interconnect in straight lines with shared posts. Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised and space is maximized. No add-on clips or "S" hooks required.
- Use corner connectors to add shelves in corners or to install intermediate shelves between 2 starter units. Unique patented design ensures maximum space utilization.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color – Brushed Graphite (580).

Project _____

Item No. _____

Model No. _____


Quantity _____



Stationary Starter Unit



Stationary Add-On Unit



Breakaway Dovetail Set

BASICS PLUS SERIES WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 30" – 48"	UNIT LENGTH 54" – 60"
SINGLE UNIT	Unit only	1800 lbs.	1800 lbs.
	Shelf only	700	500
	Unit with dunnage stand*	2100	2100
	Bottom shelf with dunnage stand*	1000	800
CORNER UNIT With 2 Dunnage Stands required	Unit only	1350	—
	Shelf only	300	—
	Bottom shelf with dunnage stands*	450	—

*Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Highly recommended for Starter Units 54" and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, and Identification Tags are not NSF listed.

COMPONENT



Information and specifications are subject to change without notice. Please confirm at time of order.

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.

Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com

Printed in USA. 09/17

Camshelving® Basics Plus Series

Stationary Starter & Add-On Units
4 Solid or 4 Vented and Solid Shelves
 (3 vented + 1 solid)

Project _____

Item No. _____

Model No. _____

Quantity _____


S4

4-Shelf Solid Units

Starter

Add-On

64"
HEIGHT



18"
DEPTH

LENGTH	CODE
30"	CBU183064S4
36"	CBU183664S4
42"	CBU184264S4
48"	CBU184864S4
54"	CBU185464S4
60"	CBU186064S4

LENGTH	CODE
28 1/4"	CBA183064S4
34 1/4"	CBA183664S4
40 1/4"	CBA184264S4
46 1/4"	CBA184864S4
52 1/4"	CBA185464S4
58 1/4"	CBA186064S4

21"
DEPTH

30"	CBU213064S4
36"	CBU213664S4
42"	CBU214264S4
48"	CBU214864S4
54"	CBU215464S4
60"	CBU216064S4

28 1/4"	CBA213064S4
34 1/4"	CBA213664S4
40 1/4"	CBA214264S4
46 1/4"	CBA214864S4
52 1/4"	CBA215464S4
58 1/4"	CBA216064S4

24"
DEPTH

30"	CBU243064S4
36"	CBU243664S4
42"	CBU244264S4
48"	CBU244864S4
54"	CBU245464S4
60"	CBU246064S4

28 1/4"	CBA243064S4
34 1/4"	CBA243664S4
40 1/4"	CBA244264S4
46 1/4"	CBA244864S4
52 1/4"	CBA245464S4
58 1/4"	CBA246064S4



Color: Brushed Graphite (580).

VS4

4-Shelf Units (3 Vented + 1 Solid)

Starter

Add-On



LENGTH	CODE
30"	CBU183064VS4
36"	CBU183664VS4
42"	CBU184264VS4
48"	CBU184864VS4
54"	CBU185464VS4
60"	CBU186064VS4

LENGTH	CODE
28 1/4"	CBA183064VS4
34 1/4"	CBA183664VS4
40 1/4"	CBA184264VS4
46 1/4"	CBA184864VS4
52 1/4"	CBA185464VS4
58 1/4"	CBA186064VS4

30"	CBU213064VS4
36"	CBU213664VS4
42"	CBU214264VS4
48"	CBU214864VS4
54"	CBU215464VS4
60"	CBU216064VS4

28 1/4"	CBA213064VS4
34 1/4"	CBA213664VS4
40 1/4"	CBA214264VS4
46 1/4"	CBA214864VS4
52 1/4"	CBA215464VS4
58 1/4"	CBA216064VS4

30"	CBU243064VS4
36"	CBU243664VS4
42"	CBU244264VS4
48"	CBU244864VS4
54"	CBU245464VS4
60"	CBU246064VS4

28 1/4"	CBA243064VS4
34 1/4"	CBA243664VS4
40 1/4"	CBA244264VS4
46 1/4"	CBA244864VS4
52 1/4"	CBA245464VS4
58 1/4"	CBA246064VS4

Optional Accessories

- Corner Connector Sets
- Bottom Shelf Dunnage Stands (Low or Tall)
- Shelf Identification Tags
- Wall Fastener
- Seismic Foot
- Shelf Divider Panel
- Single Shelf Security Cage
- Single Shelf Sheet Pan/Tray Rack
- Shelf Traverses (Single or Double)

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.
 Post Connectors: Reinforced nylon.
 Shelf Plates - Reinforced polypropylene with Camguard® antimicrobial.
 Corner Connectors: Reinforced nylon.
 Adjustable Foot: Reinforced nylon.
 Traverse Dovetails: Reinforced nylon.
 Post Connector Wedges: Reinforced polypropylene.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, and Identification Tags are not NSF listed.

COMPONENT

CAMBRO
 TRUSTED FOR GENERATIONS™
 www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.
 © Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.
 Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com
 Printed in USA. 09/17

BPS2

0081711