



# Camshelving® Basics Plus Series

## Stationary Starter & Add-On Units 4 Solid or 4 Vented and Solid Shelves (3 vented + 1 solid)

HEIGHT	DEPTHS	LENGTHS
1	3	6
72"	18" 21" 24"	30" 48" 36" 54" 42" 60"

- Starter Units include:**  
2 factory assembled post kits, 8 stationary shelf traverses, stationary traverse dovetails and shelf plates.
- Add-On Units include:**  
1 factory assembled post kit, 8 stationary shelf traverses, stationary traverse dovetails and shelf plates.

All units ship complete in 1 box.



### Features & Benefits

- Strong enough to handle small to medium volume foodservice operations with light to medium storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Install solid shelf on bottom to prevent water/cleaning liquid from sloshing onto products. Install on top to protect product on lower shelves from cooler condensation.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series and Elements Series. Breakaway left and right traverse dovetails snap apart and attach easily to secure shelf traverses to posts.
- Shelving Units interconnect in straight lines with shared posts. Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised and space is maximized. No add-on clips or "S" hooks required.
- Use corner connectors to add shelves in corners or to install intermediate shelves between 2 starter units. Unique patented design ensures maximum space utilization.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color – Brushed Graphite (580).

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_


Quantity \_\_\_\_\_



Stationary Starter Unit



Stationary Add-On Unit



Breakaway Dovetail Set

## BASICS PLUS SERIES WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH	UNIT LENGTH
		30" – 48"	54" – 60"
<b>SINGLE UNIT</b>	Unit only	1800 lbs.	1800 lbs.
	Shelf only	700	500
	Unit with dunnage stand*	2100	2100
	Bottom shelf with dunnage stand*	1000	800
<b>CORNER UNIT</b> With 2 Dunnage Stands required	Unit only	1350	—
	Shelf only	300	—
	Bottom shelf with dunnage stands*	450	—

\*Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Highly recommended for Starter Units 54" and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

### Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, and Identification Tags are not NSF listed.

COMPONENT



Information and specifications are subject to change without notice. Please confirm at time of order.

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.

Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com

Printed in USA. 09/17

# Camshelving® Basics Plus Series

**Stationary Starter & Add-On Units**  
**4 Solid or 4 Vented and Solid Shelves**  
 (3 vented + 1 solid)

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_


## S4

### 4-Shelf Solid Units

Starter

Add-On

**72"**  
HEIGHT



**18"**  
DEPTH

LENGTH	CODE
30"	CBU183072S4
36"	CBU183672S4
42"	CBU184272S4
48"	CBU184872S4
54"	CBU185472S4
60"	CBU186072S4

LENGTH	CODE
28 1/4"	CBA183072S4
34 1/4"	CBA183672S4
40 1/4"	CBA184272S4
46 1/4"	CBA184872S4
52 1/4"	CBA185472S4
58 1/4"	CBA186072S4

**21"**  
DEPTH

30"	CBU213072S4
36"	CBU213672S4
42"	CBU214272S4
48"	CBU214872S4
54"	CBU215472S4
60"	CBU216072S4

28 1/4"	CBA213072S4
34 1/4"	CBA213672S4
40 1/4"	CBA214272S4
46 1/4"	CBA214872S4
52 1/4"	CBA215472S4
58 1/4"	CBA216072S4

**24"**  
DEPTH

30"	CBU243072S4
36"	CBU243672S4
42"	CBU244272S4
48"	CBU244872S4
54"	CBU245472S4
60"	CBU246072S4

28 1/4"	CBA243072S4
34 1/4"	CBA243672S4
40 1/4"	CBA244272S4
46 1/4"	CBA244872S4
52 1/4"	CBA245472S4
58 1/4"	CBA246072S4



Color: Brushed Graphite (580).

## VS4

### 4-Shelf Units (3 Vented + 1 Solid)

Starter

Add-On



LENGTH	CODE
30"	CBU183072VS4
36"	CBU183672VS4
42"	CBU184272VS4
48"	CBU184872VS4
54"	CBU185472VS4
60"	CBU186072VS4

LENGTH	CODE
28 1/4"	CBA183072VS4
34 1/4"	CBA183672VS4
40 1/4"	CBA184272VS4
46 1/4"	CBA184872VS4
52 1/4"	CBA185472VS4
58 1/4"	CBA186072VS4

30"	CBU213072VS4
36"	CBU213672VS4
42"	CBU214272VS4
48"	CBU214872VS4
54"	CBU215472VS4
60"	CBU216072VS4

28 1/4"	CBA213072VS4
34 1/4"	CBA213672VS4
40 1/4"	CBA214272VS4
46 1/4"	CBA214872VS4
52 1/4"	CBA215472VS4
58 1/4"	CBA216072VS4

30"	CBU243072VS4
36"	CBU243672VS4
42"	CBU244272VS4
48"	CBU244872VS4
54"	CBU245472VS4
60"	CBU246072VS4

28 1/4"	CBA243072VS4
34 1/4"	CBA243672VS4
40 1/4"	CBA244272VS4
46 1/4"	CBA244872VS4
52 1/4"	CBA245472VS4
58 1/4"	CBA246072VS4

### Optional Accessories

- Corner Connector Sets
- Bottom Shelf Dunnage Stands (Low or Tall)
- Shelf Identification Tags
- Wall Fastener
- Seismic Foot
- Shelf Divider Panel
- Single Shelf Security Cage
- Single Shelf Sheet Pan/Tray Rack
- Shelf Traverses (Single or Double)

### Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.  
 Post Connectors: Reinforced nylon.  
 Shelf Plates - Reinforced polypropylene with Camguard® antimicrobial.  
 Corner Connectors: Reinforced nylon.  
 Adjustable Foot: Reinforced nylon.  
 Traverse Dovetails: Reinforced nylon.  
 Post Connector Wedges: Reinforced polypropylene.

### Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, and Identification Tags are not NSF listed.

COMPONENT

**CAMBRO**  
 TRUSTED FOR GENERATIONS™  
 www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.  
 © Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.  
 Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com  
 Printed in USA. 09/17

BPS4

0081711