



Camshelving® Basics Plus Series

Stationary Starter & Add-On Units 4 or 5 Vented and Solid Shelves (3 vented + 1 solid or 4 vented + 1 solid)

HEIGHT	DEPTHS	LENGTHS
1	3	6
84"	18" 21" 24"	30" 48" 36" 54" 42" 60"

- Starter Units include:**
2 factory assembled post kits, 8 or 10 stationary shelf traverses, stationary traverse dovetails and shelf plates.
 - Add-On Units include:**
1 factory assembled post kit, 8 or 10 stationary shelf traverses, stationary traverse dovetails and shelf plates.
- All units ship complete in 1 box.

Features & Benefits



- Strong enough to handle small to medium volume foodservice operations with light to medium storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Install solid shelf on bottom to prevent water/cleaning liquid from sloshing onto products. Install on top to protect product on lower shelves from cooler condensation.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series and Elements Series. Breakaway left and right traverse dovetails snap apart and attach easily to secure shelf traverses to posts.
- Shelving Units interconnect in straight lines with shared posts. Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised and space is maximized. No add-on clips or "S" hooks required.
- Use corner connectors to add shelves in corners or to install intermediate shelves between 2 starter units. Unique patented design ensures maximum space utilization.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color – Brushed Graphite (580).

Project _____

Item No. _____

Model No. _____


Quantity _____



Stationary Starter Unit



Stationary Add-On Unit



Breakaway Dovetail Set

BASICS PLUS SERIES WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH	UNIT LENGTH
		30" – 48"	54" – 60"
SINGLE UNIT	Unit only	1800 lbs.	1800 lbs.
	Shelf only	700	500
	Unit with dunnage stand*	2100	2100
	Bottom shelf with dunnage stand*	1000	800
CORNER UNIT With 2 Dunnage Stands required	Unit only	1350	—
	Shelf only	300	—
	Bottom shelf with dunnage stands*	450	—

*Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Highly recommended for Starter Units 54" and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, and Identification Tags are not NSF listed.

COMPONENT



Information and specifications are subject to change without notice. Please confirm at time of order.
© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com
Printed in USA. 09/17

Camshelving® Basics Plus Series

Stationary Starter & Add-On Units 4 or 5 Vented and Solid Shelves (3 vented + 1 solid or 4 vented + 1 solid)

Project _____

Item No. _____

Model No. _____


Quantity _____

84"
HEIGHT


VS4

4-Shelf Units (3 Vented + 1 Solid)

Starter



Add-On



18"
DEPTH

LENGTH	CODE
30"	CBU183084VS4
36"	CBU183684VS4
42"	CBU184284VS4
48"	CBU184884VS4
54"	CBU185484VS4
60"	CBU186084VS4

LENGTH	CODE
28 1/4"	CBA183084VS4
34 1/4"	CBA183684VS4
40 1/4"	CBA184284VS4
46 1/4"	CBA184884VS4
52 1/4"	CBA185484VS4
58 1/4"	CBA186084VS4

21"
DEPTH

30"	CBU213084VS4
36"	CBU213684VS4
42"	CBU214284VS4
48"	CBU214884VS4
54"	CBU215484VS4
60"	CBU216084VS4

22"	EA212484VS4
28"	EA213084VS4
34"	EA213684VS4
40"	EA214284VS4
46"	EA214884VS4
52"	EA215484VS4

24"
DEPTH

30"	CBU243084VS4
36"	CBU243684VS4
42"	CBU244284VS4
48"	CBU244884VS4
54"	CBU245484VS4
60"	CBU246084VS4


22"	EA242484VS4
28"	EA243084VS4
34"	EA243684VS4
40"	EA244284VS4
46"	EA244884VS4
52"	EA245484VS4

Color: Brushed Graphite (580).


VS5

5-Shelf Units (4 Vented + 1 Solid)

Starter



Add-On



LENGTH	CODE
30"	CBU183084VS5
36"	CBU183684VS5
42"	CBU184284VS5
48"	CBU184884VS5
54"	CBU185484VS5
60"	CBU186084VS5

LENGTH	CODE
28 1/4"	CBA183084VS5
34 1/4"	CBA183684VS5
40 1/4"	CBA184284VS5
46 1/4"	CBA184884VS5
52 1/4"	CBA185484VS5
58 1/4"	CBA186084VS5

30"	CBU213084VS5
36"	CBU213684VS5
42"	CBU214284VS5
48"	CBU214884VS5
54"	CBU215484VS5
60"	CBU216084VS5

28 1/4"	CBA213084VS5
34 1/4"	CBA213684VS5
40 1/4"	CBA214284VS5
46 1/4"	CBA214884VS5
52 1/4"	CBA215484VS5
58 1/4"	CBA216084VS5

30"	CBU243084VS5
36"	CBU243684VS5
42"	CBU244284VS5
48"	CBU244884VS5
54"	CBU245484VS5
60"	CBU246084VS5

28 1/4"	CBA243084VS5
34 1/4"	CBA243684VS5
40 1/4"	CBA244284VS5
46 1/4"	CBA244884VS5
52 1/4"	CBA245484VS5
58 1/4"	CBA246084VS5

Optional Accessories

- Corner Connector Sets
- Bottom Shelf Dunnage Stands (Low or Tall)
- Shelf Identification Tags
- Wall Fastener
- Seismic Foot
- Shelf Divider Panel
- Single Shelf Security Cage
- Single Shelf Sheet Pan/Tray Rack
- Shelf Traverses (Single or Double)

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.
 Post Connectors: Reinforced nylon.
 Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.
 Corner Connectors: Reinforced nylon.
 Adjustable Foot: Reinforced nylon.
 Traverse Dovetails: Reinforced nylon.
 Post Connector Wedges: Reinforced polypropylene.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, and Identification Tags are not NSF listed.

COMPONENT

CAMBRO
TRUSTED FOR GENERATIONS™
www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.
 © Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.
 Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003 Email: customerservice@cambro.com
 Printed in USA. 09/17

BPS7

0081711